


**DE452569**  
 TEMPOMATIC SHOWER KIT

**DELABIE**



**DESCRIPTION**

DELABIE DE452569 is a recessed electronic shower kit for mixed water supply by 230/12V mains power supply with transformer and M1/2" solenoid valve. Two operation modes: 1) automatic activation using presence detection, 2) Voluntary on/off activation by passing the hand in front of sensor ~10cm. Anti-bacterial duty flush operates for ~60 seconds every 24 hours after last use. Adjustable time flow from 30 to 60 seconds. Flow rate is pre-set at 6L/min at 300kPa, can be adjusted from 1.5 to 6L/min. Operating pressure is 100-500kPa, 300kPa is recommended. Chrome-plated solid brass sensor surround and ROUND shower head, tamperproof, with hygienic scale-resistant nozzle and automatic flow rate limiter.

We recommend installing a thermostatic mixing valve (see Water Tempering section).

**INSTALLATION**

Control module must be installed within 1.2m of solenoid valve. Sensor can be installed up to 5m from control module.

Water to solenoid valve should be pre-mixed to a nominal 41C using a quality thermostatic mixing valve such as Delabie Pre-Mix Confort (refer separate information).

Flow rate is dictated by shower head. Delabie commercial shower heads achieve 6L/min flow rate meeting a 3 star WELS rating.

**MODELS**

- DE452569** - Shower kit with ROUND shower head 6L/min - 3 star rating.
- DE452565** - Same as DE452569 but without shower head.
- DE452159** - Same as DE452569 but for through wall < 155mm - 3 star rating.
- DE452150** - Same as DE452159 but without shower head.