



DE746410
TEMPOSTOP
TIME FLOW BIB TAP LEVER OPERATED

DELABIE



DESCRIPTION

DELABIE DE746410 is a wall mounted time flow basin tap with lever operation. Lever operation allows users to operate the controls with no effort especially elderly or people with reduced physical ability. Time flow is ~7 seconds. Flow rate is pre-set at 3L/min at 300kPa, can be adjusted from 1.5 to 6L/min. Operating pressure is 100-500kPa, 300kPa is recommended. Chrome-plated solid brass body with tamperproof scale-resistant flow straightener and M1/2" fixing.

Supplied with red and blue indicators.

We recommend installing a thermostatic mixing valve (see Water Tempering section).

Note: Not recommended for use in early childhood facilities. Refer instead to Temposoft DE741500 or DE74100.

INSTALLATION

- Wall mounted connection M1/2".
- M1/2" water supply connection.
- For cold or tempered single water supply.
- Maximum Hot water temperature 55°C, recommended tempered supply of ~40°C.
- Flow rate pre-set at 3L/min at 300kPa, can be adjusted from 1.5 to 6L/min by using a 2.5mm Allen key directly onto the screw head located under the lever cover.

MODELS

DE746410 - Standard model 3L/min - 6 star WELS rating.

DE822516 - Extension MF1/2" L.50mm.

DE292015 - Wall plate for tap 1/2" Ø60mm.

