DE790350 TEMPOMIX SHOWER PANEL WITH SLIDE SET


DELABIE



DESCRIPTION

DELABIE DE790310 is a time flow shower panel with fixed slide shower set. Aluminium epoxy coated shower panel for surface mounting. Temperature control and operation on the push button with adjustable maximum temperature limiter. Top water inlet supply with in-line stopcocks. Sliding shower set with 720mm slide rail, L.1.50m flexible hose and chrome plated single jet shower head with non-slip grip. Time flow \sim 30 seconds with soft touch operation. Flow rate 12L/min at 300kPa. Operating pressure 100-500kPa, 300kPa is recommended.

Supplied with non-return valves, filters, fixings and M1/2" in-line stopcocks.



INSTALLATION

- Surface mounted shower panel with soft touch operation and slide shower set.
- Top inlet supply with in-line M1/2" stopcocks.
- Sliding handset on chrome plated rail with flexible hose.
- Panel screw fixes to wall in position to acheive desired
- Flow rate 12L/min at 300kPa.
- Operating water pressure 100-500kPa.
- Adjustable spray angle can be locked in place.

MODELS

DE790350 - Standard model 12L/min - 2 star WELS ratina.



Auckland (Head Office)

20 Carr Rd, Three Kings Auckland 1041 **P**: 09 624 1115 **F**: 09 624 1110

E: sales@macdonaldindustries.co.nz

Wellington

P: 04 569 8033

Christchurch

P: 03 348 2356 **F**: 04 569 8066 **F**: 03 348 2376