MACDONALD INDUSTRIES LIMITED TECHNICAL DATA SHEET

DE790925 TEMPOMIX TIME FLOW SHOWER MIXER


DELABIE



DESCRIPTION

DELABIE DE790925 is a recessed time flow shower mixer with soft touch operation. Soft touch operation allows users to use the controls with no effort especially children, elderly or people with reduced physical ability. Temperature control and operation on the push button with adjustable maximum temperature limiter. Chrome-plated Ø195mm wall plate. Recessing depth is adjustable from 28-43mm. Time flow is ~30 seconds. Flow rate is pre-set at 12L/min at 300kPa, but when connected with a Delabie shower head the actual flow rate will be 6L/min. Operating pressure is 100-500kPa, 300kPa is recommended.

Supplied with integrated non-return valves and filters.



INSTALLATION

- Recessing depth adjustable 28-43mm.
- Concealed fixings, stopcocks M1/2", integrated non-returns and filters.
- Maximum Hot water temperature 55°C.
- Maximum HW CW pressure differential 15%.
- Flow rate pre-set at 12L/min at 300kPa, actual flow rate is determined by shower head installed.
- Operating pressure 100-500kPa, 300kPa recomended.

MODELS

DE790925 - Standard model 12L/min - 2 star WELS rating.



Auckland (Head Office)

20 Carr Rd, Three Kings Auckland 1041 P: 09 624 1115 F: 09 624 1110 E: sales@macdonaldindustries.co.nz Wellington P: 04 569 8033 F: 04 569 8066 **Christchurch P**: 03 348 2356 **F**: 03 348 2376