MACDONALD INDUSTRIES LIMITED TECHNICAL DATA SHEET

DE795000 TEMPOMIX TIME FLOW BASIN MIXER


DELABIE



DESCRIPTION

DELABIE DE795000 is a deck mounted single control time flow basin mixer with a soft-touch operation. Soft touch operation allows users to use the controls with no effort especially children, elderly or people with reduced physical ability. Temperature control and operation on the ergonomic chrome-plated metal push button with adjustable maximum temperature limiter. Time flow is ~7 seconds. Flow rate is pre-set at 3L/min at 300kPa, can be adjusted from 1.5 to 6L/min. Operating pressure is 100-500kPa, 300kPa is recommended. Chrome-plated solid brass body with scale-resistant flow straightener and reinforced fixing.

Supplied with PEX flexible connectors, filters, non-return valves and M1/2'' stopcocks.



INSTALLATION

- Deck mounted through Ø34mm hole.
- Reinforced fixation using 2x stainless steel fixing screws and support ring.
- 400mm PEX flexibles connect to 1/2" water supply.
- Equal Hot & Cold supply pressure (max 15% variation).
- Maximum Hot water temperature 55°C.
- Water saving up to 85%.
- Flow rate pre-set at 3L/min at 300kPa, can be adjusted from 1.5 to 6L/min by using a 2.5mm Allen key directly on the flow straightener.

MODELS

DE795000 - Standard model 3L/min - 6 star WELS rating. **DE795100** - Same as DE795000 but without stopcocks.



Auckland (Head Office)

20 Carr Rd, Three Kings Auckland 1042 09 624 1115 sales@macdonaldindustries.co.nz macdonaldindustries.co.nz

Christchurch

32B Hayton Road Wigram, Christchurch 03 348 2356 christchurch@macdonaldindustries.co.nz

Wellington

04 569 8033